secabo

Overview

The new Secabo T160 II cutting plotter with modern automatic functions is ideal for editing large plots and large quantities in professional quality. The integrated multi-registration mark recognition system LAPOS Q automatically registers set registration marks, so that even free forms can be precisely cut. With its powerful servo motor, all common materials can be processed. An automatic media recognition adjusts the software to the inserted film width. The backlit LCD display and large gel buttons make the application easy and convenient. The Secabo T160 II vinyl cutter is designed for a maximum media width of 175 centimeters and a maximum cutting width of 160 centimeters. The scope of supply includes the cutting software DrawCut PRO for Windows as well as a stable stand with roll holder, a practical collection basket and automatic film handling for jerk-free feeding even of large and heavy rolls.

Features

Easy menu navigation

comfortable control panel with illuminated LCD-display and large buttons

DrawCut PRO

DrawCut PRO included - with control for LAPOS XPT, vectorization, text to path, shading, etc.

automatic vinyl feeding

The film is - controlled by a light sensor - automatically unwound and fed into the cutter.

high precision

High precision for cutting of smallest fonts and objects.

servo drives

silent, precise and powerful servo drives for best cutting results

Plug and play

simple installation, no additional drivers necessary

64bit enabled

The device can be controlled by 64bit operating systems.

Mac compatible

This product is also available as a mac compatible version with the SignCut software (without LAPOS).

Low noise

low noise level which makes working in an office environment possible

LAPOS Q

State-of-the-art contour cutting function for Print&Cut applications, automatic continuous recognition of register marks

Technical Data

|	
dimensions	192cm x 26cm x 26cm
weight without packaging	50 kg
Weight with packaging and stand	65 kg
scope of delivery	Cutting plotter, multilingual cutting software DrawCut PRO (Windows), drag knife, ball-bearing knife holder, plotter, plotter DIN A3, connection cable, stand with roll holder, automatic film handling and collection basket, German user manual
control	back-illuminated graphic LCD display with gel buttons
countour cutting function	LAPOS Q, sequential cut marks
max. downforce	50 - 750 g
max. media width	1750 mm
max. media thickness	1 mm
max. cutting size	1600 mm
max. cutting speed	960 mm/s
mech. resolution	0,01254 mm
interfaces	USB
motor	servomotor
Brand	Secabo

Views